

PRODUCT DESCRIPTION


The AA-1 remote audible alarm is ideal for providing audible indication at station that is remote to where the monitoring is done. The AA-1 is powered with up to 48 Vdc and provides an adjustable audible alarm up to 95 db. The AA-1 is provided on a stainless steel plate which can be mounted to a single gang utility box or directly on the wall.

TYPICAL INSTALLATION


For complete installation and wiring details, please refer to the product installation instructions.

The AA-1 series can be flush mounted directly to a single gang electrical box or directly to a wall using wall anchors.

Quick connect blades with screws are provided for connection to the monitored device or to a building automation system.



| SPECIFICATIONS | |
|--|--|
| OPERATING MODE | Medium loud medium beep tone |
| OPERATING VOLTAGE | 9-48 Vdc |
| TYPICAL OPERATING CURRENT | 5 mA at 9 Vdc, 20 mA at 48 Vdc |
| TYPICAL SOUND PRESSURE (VOLUME CONTROL OPEN) | 85 ± 5 dB(A), at 9 Vdc, at 61 cm (24"), at 25° C 95 ± 5 dB(A), at 48 Vdc, at 61 cm (24"), at 25° C |
| TERMINATION | Quick connect blades with screws |
| TERMINATION STRENGTH | Pull test with a maximum of 10 kg (22 lb) load |
| OPERATING TEMPERATURE | -20 to 65°C (-4 to 149°F) |
| SURGE VOLTAGE | 20% over maximum rated voltage for less than 5 minutes |
| REVERSE VOLTAGE PROTECTION | To the maximum operating voltage |
| CONSTRUCTION MATERIALS | Case: Plastic "NORYL®N-190", Flame Retardant UL 94-VO, Black Internal Circuit: Audio-oscillator and piezoelectric driver Potting: 2 parts epoxy resin or silicone, black Diaphragm: Stainless steel 304 Plate: Stainless steel 304 |
| ENVIRONMENTAL DURABILITY | NEMA4X Certified (IP65) |
| LIFE EXPECTANCY | 10 years under normal operating conditions |
| MOUNTING | Panel mounted on a single gang, stainless steel wall plate with volume control |



ORDERING

PRODUCT AA-1 Remote Audible Alarm

NOTE: Greystone Energy Systems, Inc. reserves the right to make design modifications without prior notice.









Greystone Energy Systems, Inc. 150 English Drive, Moncton, New Brunswick, Canada E1E 4G7 Ph: +1 (506) 853-3057 Fax: +1 (506) 853-6014 North America: 1-800-561-5611 E-mail: mail@greystoneenergy.com

AA-1

PART NUMBER