## THERMOWELLS





**T2 SERIES** 

#### **PRODUCT DESCRIPTION**

The T2 series thermowell are available in 304 series and 316 series stainless steel. They are available in a wide range of lengths. Custom lengths and materials are also available.

#### **TYPICAL INSTALLATION**

The T2 series thermowell can be installed in various locations throughout the pipe, see the diagram below.

The required torque for the set-screw to ensure secure attachment and avoid damage to the probe is 5"/lbs.



Thermowell placement in pipe

ORDERING			PART NUMBER
PRODUCT	T2	Thermowell with Set Screw	Т2
EXTERNAL THREAD SIZE	1/2	1/2"	
EXTERNAL THREAD TYPE	N B	NPT BSPT	
LENGTH	2 4 6 8 12 18	50 mm (2") 100 mm (4") 150 mm (6") 200 mm (8") 300 mm (12") 450 mm (18")	
MATERIAL	P R	304 Series stainless steel 316 Series stainless steel	

NOTE: Greystone Energy Systems, Inc. reserves the right to make design modifications without prior notice.

SPECIFICATIONS				
MATERIAL	P: 304 Series stainless steel R: 316 Series stainless steel			
LENGTH	2", 4", 6", 8", 12", & 18" Standard Custom lengths available			
THREAD SIZE	1/2" NPT or BSPT			
CONSTRUCTION	Machined construction			
COUNTRY OF ORIGIN	India			

# T2 THERMOWELL PRESSURE AND FLOW SPECIFICATIONS

	DESCRIPTION	MAXIMUM FLOW @ 750°F (400°C)				MAXIMUM PRESSURE			
PART NUMBER		AIR AND STEAM		WATER		AT 200°F (100°C)		AT 750°F (400°C)	
		ft/s	m/s	ft/s	m/s	PSI	BAR	PSI	BAR
T2 - 1/2 (X) 2P	2" (50mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S		19.8	48	14.6				
T2 - 1/2 (X) 4P	4" (100mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S	65	19.8	48	14.6		433	3805	263
T2 - 1/2 (X) 6P	6" (150mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S	49	14.9	37	11.2	6200			
T2 - 1/2 (X) 8P	8" (200mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S	32	9.7	24	7.3	0290			
T2 - 1/2 (X) 12P	12" (300mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S	12	3.6	12	3.6				
T2 - 1/2 (X) 18P	18" (450mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 304 S/S	4	1.2	4	1.2				
T2 - 1/2 (X) 2R	2" (50mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	63	19.2	48	14.6		456	5500	380
T2 - 1/2 (X) 4R	4" (100mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	63	19.2	48	14.6	6615			
T2 - 1/2 (X) 6R	6" (150mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	47	14.3	37	11.2				
T2 - 1/2 (X) 8R	8" (200mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	31	9.4	24	7.3				
T2 - 1/2" (X) 12R	12" (300mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	12	3.6	12	3.6				
T2 - 1/2"(X) 18R	18" (450mm), 1/2" NPT/BSP, 0.026" (6mm) Bore, 316 S/S	4	1.2	4	1.2				

### NOTE

(X) = N for NPT, B for BSP

1) These are worst-case velocity ratings for air, steam, and water. Based on air at 21°C (70°F), 6900 PSI (475 Bar), with a density of 35 lb/ft<sup>3</sup> (560 kg/m<sup>3</sup>), steam at 400°C (750°F), 5500 PSI (379 Bar), with a density of 32 lb/ft<sup>3</sup> (512 kg/m<sup>3</sup>), and water at 21°C (70°F), [6800 PSI (468 Var) for 316 S/S], with a density of 63.59 lb/ft<sup>3</sup> (1018 kg/m<sup>3</sup>). Significantly higher velocities are possible when fluid/gases at lower densities.

2) Specification of a thermowell and the materials of construction are the sole responsibility of the designer of the system that incorporates the thermowell. Sole responsibility for ensuring compatibility of the process fluid with the system rests with the end user.

3) These ratings do not consider corrosion.



Greystone Energy Systems, Inc. 150 English Drive, Moncton, New Brunswick, Canada E1E 4G7 Ph: +1 (506) 853-3057 Fax: +1 (506) 853-6014 North America: 1-800-561-5611 E-mail: mail@greystoneenergy.com