



Temp (Deg C)	Res (Ohms)	Temp (Deg F)	Temp (Deg C)	Res (Ohms)	Temp (Deg F)	Temp (Deg C)	Res (Ohms)	Temp (Deg F)
-40.0	4070000	-40.0	14.0	169900	57.2	68.0	16690	154.4
-39.0	3798000	-38.2	15.0	161700	59.0	69.0	16080	156.2
-38.0	3546000	-36.4	16.0	153900	60.8	70.0	15500	158.0
-37.0	3312000	-34.6	17.0	146500	62.6	71.0	14940	159.8
-36.0	3095000	-32.8	18.0	139600	64.4	72.0	14410	161.6
-35.0	2893000	-31.0	19.0	133000	66.2	73.0	13900	163.4
-34.0	2706000	-29.2	20.0	126700	68.0	74.0	13410	165.2
-33.0	2532000	-27.4	21.0	120800	69.8	75.0	12930	167.0
-32.0	2369000	-25.6	22.0	115200	71.6	76.0	12480	168.8
-31.0	2218000	-23.8	23.0	109800	73.4	77.0	12050	170.6
-30.0	2078000	-22.0	24.0	104800	75.2	78.0	11630	172.4
-29.0	1946000	-20.2	25.0	100000	77.0	79.0	11230	174.2
-28.0	1824000	-18.4	26.0	95450	78.8	80.0	10840	176.0
-27.0	1710000	-16.6	27.0	91120	80.6	81.0	10470	177.8
-26.0	1604000	-14.8	28.0	87020	82.4	82.0	10110	179.6
-25.0	1505000	-13.0	29.0	83120	84.2	83.0	9769	181.4
-24.0	1413000	-11.2	30.0	79420	86.0	84.0	9439	183.2
-23.0	1327000	-9.4	31.0	75900	87.8	85.0	9122	185.0
-22.0	1247000	-7.6	32.0	72560	89.6	86.0	8817	186.8
-21.0	1173000	-5.8	33.0	69380	91.4	87.0	8524	188.6
-20.0	1103000	-4.0	34.0	66360	93.2	88.0	8241	190.4
-19.0	1038000	-2.2	35.0	63480	95.0	89.0	7969	192.2
-18.0	977600	-0.4	36.0	60740	96.8	90.0	7708	194.0
-17.0	920900	1.4	37.0	58140	98.6	91.0	7456	195.8
-16.0	867700	3.2	38.0	55660	100.4	92.0	7213	197.6
-15.0	818000	5.0	39.0	53300	102.2	93.0	6979	199.4
-14.0	771300	6.8	40.0	51050	104.0	94.0	6754	201.2
-13.0	727600	8.6	41.0	48910	105.8	95.0	6538	203.0
-12.0	686500	10.4	42.0	46860	107.6	96.0	6329	204.8
-11.0	648000	12.2	43.0	44920	109.4	97.0	6129	206.6
-10.0	611900	14.0	44.0	43060	111.2	98.0	5935	208.4
-9.0	578000	15.8	45.0	41290	113.0	99.0	5749	210.2
-8.0	546100	17.6	46.0	39600	114.8	100.0	5569	212.0
-7.0	516100	19.4	47.0	37990	116.6	101.0	5396	213.8
-6.0	488000	21.2	48.0	36460	118.4	102.0	5230	215.6
-5.0	461500	23.0	49.0	34990	120.2	103.0	5069	217.4
-4.0	436700	24.8	50.0	33590	122.0	104.0	4914	219.2
-3.0	413300	26.6	51.0	32250	123.8	105.0	4764	221.0
-2.0	391200	28.4	52.0	30980	125.6	106.0	4620	222.8
-1.0	370500	30.2	53.0	29760	127.4	107.0	4480	224.6
0.0	351000	32.0	54.0	28590	129.2	108.0	4346	226.4
1.0	332600	33.8	55.0	27470	131.0	109.0	4216	228.2
2.0	315300	35.6	56.0	26410	132.8	110.0	4090	230.0
3.0	298900	37.4	57.0	25390	134.6	111.0	3969	231.8
4.0	283600	39.2	58.0	24410	136.4	112.0	3852	233.6
5.0	269000	41.0	59.0	23480	138.2	113.0	3738	235.4
6.0	255300	42.8	60.0	22590	140.0	114.0	3629	237.2
7.0	242400	44.6	61.0	21740	141.8	115.0	3523	239.0
8.0	230200	46.4	62.0	20920	143.6	116.0	3421	240.8
9.0	218700	48.2	63.0	20130	145.4	117.0	3322	242.6
10.0	207800	50.0	64.0	19380	147.2	118.0	3227	244.4
11.0	197500	51.8	65.0	18670	149.0	119.0	3134	246.2
12.0	187800	53.6	66.0	17980	150.8	120.0	3045	248.0
13.0	178600	55.4	67.0	17320	152.6			

NOTE: Temperature cycling below -25 Deg. C or above +125 Deg. C is not recommended.

Sensor tolerance is +/- 0.2 Deg. C in the range 0-70 Deg. C.