

INDOOR AIR QUALITY & GAS DETECTION PRODUCT SERIES

275

GREYSTOME

* 4 8

GREYSTON



A comprehensive selection of air quality & gas measuring products that are designed and manufactured for long-term stability and performance. Each product provides a repeatable and accurate output signal for efficient air quality & gas monitoring and control.

PRODUCTS

- Carbon Dioxide
- Carbon Dioxide, RH, & Temperature
- Particulate Matter
- Volatile Organic Compounds
- Carbon Monoxide
- Nitrogen Dioxide
- Duct Smoke Detector



GREYSTONE HAS AN ISO 9001 REGISTERED QUALITY SYSTEM

AIR & GAS

IAQ MULTI-SENSE



FEATURES

- Measures 5 or 6 parameters
- Field replaceable sensor modules
- BACnet[®] or Modbus communications
- Full-colour configurable touchscreen LCD
- Configurable alarm relay
- Modern, quick-mount enclosure

CARBON DIOXIDE

CE, CD, CDD4 Series



PRODUCT TYPES

- Room
- Duct
- Outside

FEATURES

- Menu driven set-up
- 0-2,000 scalable to 10,000 PPM CO2
- NDIR, dual channel
- Optional temperature sensor outputs
- Guaranteed 5 year calibration interval
- Easily field calibrated

CARBON DIOXIDE, TEMPERATURE AND HUMIDITY

CDD3, CDD5, CHT Series



PRODUCT TYPES

- Room
- Duct

FEATURES

- Outputs CO2, Temperature, & RH Levels
- Menu driven set-up
- 0-2,000 scalable to 10,000 PPM CO2
- NDIR, dual channel
- Guaranteed 5 year calibration level
- Easily field calibrated
- Analog, BACnet[®] or Modbus output



PARTICULATE MATTER

PM Series



PRODUCT TYPES

- Room
- Duct
- Outside

FEATURES

- Selectable PM1, 2.5, 4 & 10 Particle Sizes
- 0 1000 ug/m3 range
- LCD displaying PM level
- Tri-color LED to indicate IAQ level
- Analog, BACnet[®] or Modbus output
- Field replaceable sensor

VOLATILE ORGANIC COMPOUNDS

VOC Series



PRODUCT TYPES

- Room
- Duct

FEATURES

- VOC Index value scale
- Tri-color LED to indicate IAQ level
- LCD display
- Analog, BACnet[®] or Modbus output
- Optional humidity and temperature



CARBON MONOXIDE/ NITROGEN DIOXIDE

GDT, CMD, NDD Series



PRODUCT TYPES

- Surface
- Duct

FEATURES

- Selectable ranges up to 500 ppm CO or 10 ppm NO2
- Single or dual gas monitoring
- Combination or remote sensor
- Replaceable electrochemical sensing pods
- Analog, BACnet[®] or Modbus output
- Optional alarm relays with field adjustable trip point
- Optional audible and visual alarm indication
- Optional temperature output
- Easy to calibrate in the field

DUCT SMOKE DETECTOR

DSD Series



PRODUCT TYPES

• Duct

FEATURES

- Simple change-out of photoelectric detector heads
- Low flow air velocity rating from 100 to 4000 FPM
- UL, CSFM, and MEA listed
- Two sets of 10A form "C" alarm contacts
- One set of 10A form "C" trouble contacts
- Clear cover for convenient visual inspection
- Built-in reset switch/alarm test switch



Phone : +1-506-853-3057 North America: +1-800-561-5611 www.greystoneenergy.com



