

The LP3 series is used to measure positive, negative or differential pressure. The piezoresistive sensor is ideal for monitoring the pressure of air or other clean inert gas. Typical HVAC applications include monitoring of filter differential pressure or VAV applications. An integrated static pressure probe provides ease of installation for duct mounting. Several accessories are available.

#### **SPECIFICATION:**

Accuracy±	1% F.S.O.
Measurement TypeDi	ifferential (two port), Static,
Ve	elocity, & Total Pressure
Response Time25	50 ms
Stability<	
Thermal Effects<	±3% over compensated range
Compensated Range0	
	0" W.C. (100" for 10" & 20" Models)
	0" W.C. (200" for 10" & 20" Models)
Operating Conditions0	
	0 - 90 %RH, non-condensing
Power Supply20	) - 28 Vac/dc
(n	on-isolated half-wave rectified)
Supply Current<	4 mA
	egligible over operating range
Protection CircuitryRe	
OL	utput limited
Output Signal4-	20 mA (2-wire), 0-5 or
0-	10 Vdc (3-wire), switch selectable
Output Drive CapabilitiesCu	urrent: 400 ohms max @ 24 vdc
	oltage: 10K ohms min
Zero AdjustmentsPu	ushbutton auto-zero
Wiring ConnectionsSo	crew terminal block (14 to 22 AWG)
Pressure ConnectionBa	arbed ports for 5 mm (0.170" ID)
fle	exible tubing
Conduit Connection	"NPT concuit or cable gland
Optional Display	
EnclosuresAl	BS, plenum rated
Weight15	59 grams (5.6 oz)

### **TYPICAL INSTALLATION:**

# For complete installation and wiring details, please refer to the product installation instructions.

The LP3 mounts on any surface using the two holes provided on the base of the unit. Make sure there is enough space around the unit to connect the pressure tubing without kinking and avoid locations where severe vibrations or excessive moisture are present.

The unit may be mounted in any position but typically is installed on a vertical surface with pressure ports on the right and the cable entrance on the left. If the unit has the integrated static pressure probe, drill a hole in the duct and insert so the probe point is facing into the airflow. The enclosure has a standard opening for a 1/2" conduit and may be installed with either conduit and a conduit coupler or a cable gland type fitting.


## LOW PRESSURE TRANSMITTER LP3 Series

GREYSTONE

PART NUMBER SELECTED

MODEL LP3	Product Low Pres	essure Transmitter			
	CODE A B	Options Standard LCD Display			
			Range ±1", ±2", ±4", 0-1", 0-2", 0-4" W.C. ±3", ±5", ±8", 0-3", 0-5", 0-8" W.C. ±6", ±10", ±12", 0-6", 0-10", 0-12" W.C. ±10", ±15", ±20", 0-10", 0-15", 0-20" W.C. ±250, ±500, ±1000, 0-250, 0-500, 0-1000 Pa ±500, ±1000, ±2000, 0-500, 0-1000, 0-2000 Pa		
		05	CODE	Options Integrated Static Pressure Probe	

Greystone Energy Systems, Inc. reserves the right to make design modifications without prior notice.





### DIMENSIONS



12/13

GREYSTONE HAS AN ISO 9001 REGISTERED QUALITY SYSTEM